



Features:

- Industry Leading LED diodes
- High Performance Drivers
- 5-year warranty
- TM-21, LM-79, LM-80, ISTMT (6000 hour test)
- Includes Rough In Plate
- 0-10V Dimming
- Battery Backup Optional
- Easy Install in new Construction or Renovation



Model	Description	Watts	Lumens	LPW	Equiva- lent	Beam Angle	CCT	CRI	Size	Life Span	Dimmable	Voltage	Energy Star
AGL-SDL-6-20	6" Square 20W Down Light	20	1880	94	60W	90°	3000K-4000K-5000K	92	6"x6"	50000	0-10V	120-277V	Yes
AGL-SDL-6-25	6" Square 25W Down Light	25	2350	94	75W	90°	3000K-4000K-5000K	92	6"x6"	50000	0-10V	120-277V	Yes
AGL-SDL-8-30	8" Square 30W Down Light	30	2800	94	90W	90°	3000K-4000K-5000K	92	8"x8"	50000	0-10V	120-277V	Yes
AGL-SDL-8-45	8" Square 45W Down Light	45	4230	94	100W	90°	3000K-4000K-5000K	92	8"x8"	50000	0-10V	120-277V	Yes
AGL-RDL-6-15	6" Round 15W Down Light	15	1500	100	60W	90°	3000K-4000K-5000K	92	6"	50000	0-10V	120-277V	Yes
AGL-RDL-6-20	6" Round 20W Down Light	20	2000	100	75W	90°	3000K-4000K-5000K	92	6"	50000	0-10V	120-277V	Yes
AGL-RDL-8-36	8" Round 36W Down Light	36	3600	100	100W	90°	3000K-4000K-5000K	92	8"	50000	0-10V	120-277V	Yes