



Features:

- Industry Leading LED diodes
- Clean, Stylish, Contemporary Design
- CCT adjustable from 3000K, 4000K or 5000K with switch
- Dimmable 0-10V & PWM
- Emergency driver optional
- Easy Installation
- Dust Free Design IP40
- Save an average of 50% energy over T-8/T-12 fluorescent
- Clean even light distribution
- Surface, Recessed and Suspended mounting options
- 5-year warranty



Model	Description	Watts	Lumens	LPW	Equivalent	CCT	CRI	Size	Life Span	Dimmable	Voltage	DLC
AGL-U4A25-P6	2x2 25W Panel CCT Select	25	3250	130	2L T12U	3000K-4000K-5000K	80	2x2Ft	50000	0-10V or PWM	120-277V	Yes
AGL-U4A36-P6A	2x2 36W Panel CCT Select	36	4680	130	2L T8U	3000K-4000K-5000K	80	2x2Ft	50000	0-10V or PWM	120-277V	Yes
AGL-U3A32-P6/A	1x4 32W Panel CCT Select	36	4160	130	2L T8	3000K-4000K-5000K	80	1x4Ft	50000	0-10V or PWM	120-277V	Yes
AGL-U3A36-P6	1x4 36W Panel CCT Select	36	4680	130	2L T8	3000K-4000K-5000K	80	1x4Ft	50000	0-10V or PWM	120-277V	Yes
AGL-U5A40-P6	2x4 40W Panel CCT Select	40	5200	130	2-3L T8	3000K-4000K-5000K	80	2x4Ft	50000	0-10V or PWM	120-277V	Yes
AGL-U5A70-P6	2x4 70W Panel CCT Select	70	7000	100	4L T8	3000K-4000K-5000K	80	2x4Ft	50000	0-10V or PWM	120-277V	Yes