

Features:

- Industry Leading LED diodes
- High Performance Drivers
- Frame-less design
- Slim modern look
- Clean even light distribution
- Dimmable design with remote control dimmer
- Anti-glare design
- No UV or IR radiation



Model	Description	Watts	Lumens	LPW	Beam Angle	CCT	CRI	Size	Life Span	Dimmable	Voltage
AGL-AR-Pendant-TGY-40-27K-D	Decorative Pendant	40	2000	50	180°	2700K	80	13.5"x4'	50000	Yes	120-277V
AGL-AR-Pendant-TGY-40-30K-D	Decorative Pendant	40	2000	50	180°	3000K	80	13.5"x4'	50000	Yes	120-277V
AGL-AR-Pendant-TGY-40-40K-D	Decorative Pendant	40	2000	50	180°	4000K	80	13.5"x4'	50000	Yes	120-277V
AGL-AR-Pendant-TGY-40-65K-D	Decorative Pendant	40	2000	50	180°	6500K	80	13.5"x4'	50000	Yes	120-277V
AGL-AR-Pendant-YZ-42-27K-D	Decorative Pendant	40	2000	47.5	180°	2700K	80	13.5"x4'	50000	No	120-277V
AGL-AR-Pendant-YZ-42-30K-D	Decorative Pendant	40	2000	47.5	180°	3000K	80	13.5"x4'	50000	No	120-277V
AGL-AR-Pendant-YZ-42-40K-D	Decorative Pendant	40	2000	47.5	180°	4000K	80	13.5"x4'	50000	No	120-277V
AGL-AR-Pendant-YZ-42-65K-D	Decorative Pendant	40	2000	47.5	180°	6500K	80	13.5"x4'	50000	No	120-277V